



CONDITIONS OF APPLICATION

Solution: Mineralspray packaged in can 5L

Utilization: Fixing aggregates and wood chips in flowerbeds and mulching for non-circulated surfaces.

Storage conditions for ready-to-use containers:

- Store indoors, shielded from direct sunlight, at a temperature between 5°C and 30°C.
- Use within an optimal shelf life of 1 year after production.

Weather conditions:

- Application and drying should occur in dry weather with an outdoor temperature preferably between 15°C and 30°C.
- No precipitation expected within 10 hours after application.
- · Avoid application during potential freezing periods.
- · Morning application is recommended.

Surface preparation:

• The surface must be dry and free of dust.

Application:

- · Shake before use.
- Use Mineralspray® with a manual or electric sprayer.
- An watering can can also be used, but be cautious not to overapply.
- Spray the solution on the area at a dosage of approximately 0.3 to 0.5 liters per square meter as needed.
- Overapplication may result in yellowing of light-colored aggregates.
- Drying time: 2 to 10 hours at temperatures above 15°C without precipitation.
- Rinse and clean the sprayer with water immediately after use.





Additional factors to consider:

- Wind can impact the drying process.
- Remember to turn off automatic sprinklers near the application site during application and the drying phase.
- Morning dew and air humidity can prolong the drying phase.